















# ALUGOM








DATOS  
PERFILES





Ref.	Denominación	Diseño	Peso (kg)	Pe (mm)	lx cm <sup>2</sup>	ly cm <sup>2</sup>	Wx cm <sup>3</sup>	Wy cm <sup>3</sup>
<b>8958M</b>	Hoja perimetral		1.244	578.55	19.56	13.57	4.755	5.635
<b>8965M</b>	Cerco perimetral 110 mm		2.181	958.1	17.78	91.60	6.329	15.679
<b>8967M</b>	Cerco 3 carriles		3.183	1391.7	24.24	302.19	8.514	34.72
<b>8389M</b> <small>NO STOCK</small>	Cerco 4 carriles		4.185	1.825	31.84	704.95	2.226	12.196
<b>8962M</b>	Acople cierre multipunto		1.525	752.59	4.088	2.543	2.129	1.497
<b>8960</b>	Acople hoja central (8958M)		0.476	255.5	4.015	5.723	1.989	3.380
<b>8865M</b>	Pilastra cerco		0.951	483.99	7.663	6.717	2.863	1.972
<b>8810M</b>	Pilastra cerco ancha		1.244	622.91	10.59	20.02	4.034	4.449
<b>8963M</b>	Cerco fijo (50 RPTM)		1.525	752.59	5.75	57.44	1.757	9.356
<b>8954</b>	Tapa carril horizontal		0.206	83.14	0.101	0.085	0.110	0.128
<b>8953</b>	Vierteaguas		0.289	146.00	2.659	0.208	1.685	0.286
<b>1140</b> <b>281</b>	Solapa 30 mm		0.183	110.14	0.646	0.042	0.369	0.046
<b>8832</b>	Solapa inferior 30 mm		0.208	125.97	0.919	0.122	0.923	0.197
<b>8629</b>	Solapa 45 mm		0.231	140.1	1.81	0.047	0.746	0.049

Ref.	Denominación	Diseño	Peso (kg)	Pe (mm)	Ix cm <sup>4</sup>	Iy cm <sup>4</sup>	Wx cm <sup>3</sup>	Wy cm <sup>3</sup>
8630	Solapa inferior 45 mm		0.256	155.9	2.414	0.135	3.731	0.100
6695 783	Base refuerzo postizo hoja		0.545	180.9	1.184	1.650	0.842	1.119
6696 784	Tapa refuerzo postizo hoja		0.179	93.6	0.031	0.575	0.048	0.390
6806 628	Refuerzo postizo pilastra		1.040	287.2	7.843	11.72	5.466	11.16
6807 629	Tapa refuerzo postizo pilastra		0.283	157.4	0.170	2.420	0.158	1.152

**NO STOCK** FUERA DE STOCK Consultar plazo y condiciones de entrega